2017 Volvo S60 Specifications

	S60 T2 (122 hp) aut	S60 T3 (152 hp) man	S60 T3 (152 hp) aut	S60 T4 (190 hp) man/aut	S60 T5 (245 hp) aut	S60 T6 FWD/AWD (306 hp) aut	S60 Polestar AWD (367 hp) aut	S60 D2 (120 hp) man	S60 D2 (120 hp) aut	S60 D3 (150 hp) man/aut	S60 D4 (190 hp) man/aut	S60 D4 AWD (190 hp) aut	S60 D5 AWD (225 hp) aut
Engine													
Engines	B4154T5	B4204T37	B4154T4	B4204T19	B4204T11	B4204T9	B4204T43	D4204T8	D4204T20	D4204T9	D4204T14	D5244T21	D4204T11
Type	In-line, 4 cyl. turbocharged	In-line, 4 cyl. turbocharged	In-line, 4 cyl. turbocharged	In-line, 4 cyl. turbocharged	In-line, 4 cyl. turbocharged	In-line 4 cyl. supercharged and turbocharged	In-line 4 cyl. supercharged and turbocharged	In-line 4 cyl. turbo diesel	In-line 4 cyl. turbo diesel	In-line 4 cyl. turbo diesel	In-line 4-cyl. twin turbo diesel	In-line 5-cyl. twin turbo diesel	In-line 4-cyl. twin turbo diesel
Configuration	FWD	FWD	FWD	FWD	FWD	FWD / AWD	AWD	FWD	FWD	FWD	FWD	AWD	FWD
Displacement	1498 cm³	1969 cm³	1498 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	2400 cm³	1969 cm³
Bore	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	81,0 mm	82,0 mm
Stroke	70,9 mm	93,2 mm	70,9 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm
Compression ratio	10,5:1	11,3:1	10,5:1	11,3:1	10,8:1	10,3:1	8,6:1	16,0:1	16,0:1	16,0:1	15,8:1	16,5:1	15,8:1
Valves, no/cylinder	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.
DOHC / SOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC
Engine management system	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection
Ignition sequence	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 2 - 4 - 5 - 3	1 - 3 - 4 - 2	1 - 3 - 4 - 2
Engine idling speed	850 rpm ± 100	850 rpm ± 100	850 rpm ± 100	850 rpm ± 100	850 rpm ± 100	850 rpm ± 100	850 rpm ± 100	850 rpm ± 150	825 rpm ± 150	825 rpm ± 150	825 rpm ± 150	740 rpm ± 25	825 rpm ± 150
Fuel, rec. Octane	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]
Max engine speed	6000 rpm	6000 rpm	6000 rpm	6000 rpm	6000 rpm	6000 rpm	7000 rpm	4500 rpm	4500 rpm	4500 rpm	5000 rpm	5200 rpm	5000 rpm
Max output	90 kW (122 hp) / 5000 rpm	112 kW (152 hp) / 5000 rpm	112 kW (152 hp) / 5000 rpm	140 kW (190 hp) / 4700 rpm	180 kW (245 hp) / 5500 rpm	225 kW (306 hp) / 5700 rpm	270 kW (367 hp) / 6000 rpm	88 kW (120 hp) / 3750 rpm	88 kW (120 hp) / 3750 rpm	110 kW (150 hp) / 3750 rpm	140 kW (190 hp) / 4250 rpm	140 kW (190 hp) / 4000 rpm	165 kW (225 hp) / 4250 rpm
Max torque	220 / 27-58 Nm / rps	250 / 22-67 Nm / rps	250 / 28-67 Nm / rps	300 / 22-67 Nm / rps	350 / 25-80 Nm / rps	400 / 35-75 Nm / rps	470 / 52-85 Nm / rps	280 / 25-38 Nm / rps	280 / 25-38 Nm / rps	320 / 29-50 Nm / rps	400 / 29-42 Nm / rps	440 / 25-46 Nm / rps	470 / 29-42 Nm / rps

[1] According to EN590 Maximum biodiesel (FAME) content 7%

Transmissions													
Transmissions	AW TF-71SC	M66H	AW TF-71SC	M66H / AW TF-71SC	AW TG-81SC	AW TG-81SC	-	M66F	AW TF-71SC	M66F / AW TF-71SC	M66F / AW TG-81SC	-	AW TG-81SC
First Gear	4,044	3,385	4,044	3,583 / 4,044	5,250	5,250	-	3,583	4,044	3,583 / 4,044	3,583 / 5,250	-	5,250
Second Gear	2,371	1,952	2,371	1,952 / 2,371	3,029	3,029	-	2,050	2,371	2,050 / 2,371	2,050 / 3,029	-	3,029
Third Gear	1,556	1,267	1,556	1,267 / 1,556	1,950	1,950	-	1,267	1,556	1,267 / 1,556	1,267 / 1,950	-	1,950
Fourth Gear	1,159	0,868	1,159	0,868 / 1,159	1,457	1,457	-	0,838	1,159	0,838 / 1,159	0,838 / 1,457	-	1,457
Fifth Gear	0,852	0,652	0,852	0,652 / 0,852	1,221	1,221	-	0,617	0,852	0,617 / 0,852	0,617 / 1,221	-	1,221
Sixth Gear	0,672	0,540	0,672	0,540 / 0,672	1,000	1,000	-	0,510	0,672	0,510 / 0,672	0,510 / 1,000	-	1,000
Seventh Gear	-	-	-	-	0,809	0,809	-	-	-	-	- / 0,809	-	0,809
Eighth Gear	-	-	-	-	0,673	0,673	-	-	-	-	- / 0,673	-	0,673
Reverse Gear	3,193	2,692	3,193	2,692 / 3,193	4,015	4,015	-	2,833	3,193	2,833 / 3,193	2,833 / 4,015	-	4,015
Manual Gearbox/final drive	-	4,267	-	4,267	-	-	-	4,000	-	4,000	3,773	-	-
Automatic Gearbox/final drive	3,365	-	3,365	3,365	2,774	2,774	-	-	3,365	3,365	2,666	-	2,666
Transmissions (AWD)	-	-	-	-	-	AW TG-81SC	AW TG-81SC	-	-	-	-	AW TG-80SD	-
First Gear (AWD)	-	-	-	-	-	5,250	5,250	-	-	-	-	4,148	-
Second Gear (AWD)	-	-	-	-	-	3,029	3,029	-	-	-	-	2,370	-
Third Gear (AWD)	-	-	-	-	-	1,950	1,950	-	-	-	-	1,556	-
Fourth Gear (AWD)	-	-	-	-	-	1,457	1,457	-	-	-	-	1,155	-
Fifth Gear (AWD)	-	-	-	-	-	1,221	1,221	-	-	-	-	0,859	-
Sixth Gear (AWD)	-	-	-	-	-	1,000	1,000	-	-	-	-	0,686	-
Seventh Gear (AWD)	-	-	-	-	-	0,809	0,809	-	-	-	-	-	-
Eighth Gear (AWD)	-	-	-	-	-	0,673	0,673	-	-	-	-	-	-
Reverse Gear (AWD)	-	-	-	-	-	4,015	4,015	-	-	-	-	3,394	-
Automatic Gearbox / final drive (AWD)	-	-	-	-	-	3,075	3,329	-	-	-	-	3,075	-
Performance													
Performance	Automatic	Manual	Automatic	Manual / Automatic	Automatic	Automatic / Automatic	Automatic	Manual	Automatic	Manual / Automatic	Manual / Automatic	Automatic	Automatic
Gearbox	AW TF-71SC	M66H	AW TF-71SC	M66H / AW TF-71SC	AW TG-81SC	AW TG-81SC / AW TG-81SC	AW TG-81SC	M66F	AW TF-71SC	M66F / AW TF-71SC	M66F / AW TG-81SC	AW TG-80SD	AW TG-81SC
Acceleration, 0-100 km/h	10,2 sec	8,6 sec	8,6 sec	7,2 sec / 7,2 sec	6,3 sec	5,9 sec / 5,9 sec	4,7 sec	11,2 sec	11,4 sec	9,0 sec / 9,0 sec	7,6 sec / 7,6 sec	8,8 sec	6,4 sec
Top speed, km/h	195 km/h	210 km/h	210 km/h	230 km/h / 230 km/h	230 km/h	230 km/h / 230 km/h	250 km/h	195 km/h	195 km/h	215 km/h / 210 km/h	230 km/h / 230 km/h	230 km/h	230 km/h
Fuel consumption (EC 199/100, Combined)	5,8 l/100km	5,6 l/100km	5,8 l/100km	5,6 l/100km / 5,8 l/100km	6,2 l/100km	6,4 l/100km / 6,9 l/100km	7,8 l/100km	3,9 (3,8") l/100km [1]	4,3 (4,2") l/100km [1]	4,0 (3,9") l/100km / 4,3 (4,2") l/100km [1]	3,9 (3,8") l/100km / 4,3 (4,1") l/100km [1]	5,4 l/100km	4,5 l/100km
CO^2	134 g/km	131 g/km	134 g/km	131 g/km / 134 g/km	145 g/km	149 g/km / 161 g/km	179 g/km	102 (99") g/km [1]	113 (110") g/km [1]	105 (102") g/km / 113 (110") g/km [1]	102 (99") g/km / 113 (109") g/km [1]	143 g/km	119 g/km

[1] + = Restricted offer

Measurements and Volumes													
Length	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm
Width (Including mirrors, folded)	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm
Width (Including mirrors, outer edge)	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm
Height (Including shark fin)	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm
Wheelbase (L110)	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm
Track, front (16"/17")	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm
Track, rear (16"/17")	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm
Ground clearance	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm
Weight/Miscellaneous													
Weight (Depending on type of engine, gearbox etc.)	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg	1605 kg - 1751 kg
Total Weight (Depending on type of engine, gearbox etc.)	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2180 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg	2060 kg - 2200 kg
Max trailer weight, Unbraked (Max)	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg / 750 kg	-	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg
Max trailer weight, Braked (Max)	1500 kg	1600 kg	1500 kg	1600 kg / 1600 kg	1800 kg	1800 kg / 1800 kg	-	1600 kg	1600 kg	1600 kg / 1600 kg	1800 kg / 1800 kg	1800 kg	1800 kg
Fuel tank, Petrol	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	-	-	-	-	-	-
Fuel tank, Diesel	-	-	-	-	-	-	-	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l
Aerodynamics, (Cd)	0,28	0,28	0,28	0,28	0,28	0,28	0,28	0,28	0,28	0,28	0,28	0,28	0,28
Aerodynamics, (Frontal area)	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²	2,27 m²
Max roof load	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg
Interior Measurements													
Headroom with sunroof (front/rear)	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm	955 mm / 951 mm
Headroom without sunroof maximum (front/rear)	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm	999 mm / 951 mm
Passenger compartment width at shoulder height (front/rear)	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm	1447 mm / 1401 mm
Leg room (front/rear)	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm	1064 mm / 852 mm
Hip room (front/rear)	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm	1395 mm / 1359 mm
Cargo length at floor from the back of the front seatback	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm
Cargo length at floor from the back of the rear seatback	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm	965 mm
Lift over height	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm	656 mm
Rear opening height	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm	404 mm
Height between luggage floor and parcel shelf	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm	492 mm
Luggage floor, height to ground	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm	538 mm
Width of luggage compartment between wheelhouses	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm	919 mm
Rear opening width at floor, min.	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm	956 mm
Chassis													
Suspension front	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Polestar Coil Springs, Öhlins Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar
Suspension rear	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Polestar Coil Springs, Öhlins Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar
Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering
Steering (angle/angle)	15	15	15	15	15	15	15	15	15	15	15	15	15
Turning circle (Curb to curb) (Tire (width) 205/235/245)	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	- / - / 11,9 m	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -	11,3 m / 11,9 m / -
Turning circle (Wall to wall) (Tire (width) 205/235/245)	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	- / - / 12,4 m	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -	11,5 m / 12,4 m / -
Turns of steering wheel end to end	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58	2,71 / 2,58
Braking system	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assistance (BA)
Brake disc diameter (front) (Rim size: 16"/16.5"/17.5"/20")	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	- / - / - / 371 mm	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -	300 mm / 316 mm / 336 mm / -
Brake disc diameter (rear)	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm
Brake disc thickness (front) (Rim size: 16", 16.5", 17.5" / 20")	28 mm / -	28 mm / -	28 mm / -	28 mm / -	28 mm / -	28 mm / -	- / 32 mm	28 mm / -	28 mm / -	28 mm / -	28 mm / -	28 mm / -	28 mm / -
Brake disc thickness (rear) (Solid EPD/Ventilated EPD)	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm
Braking distance 100-0 km/h	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m