

2019 Volvo V40 Cross Country Specifications			
	V40 CC T3 (152 hp) aut	V40 CC D2 (120 hp) man/aut	V40 CC D3 (150 hp) man/aut
Engine			
Engines	B4154T2	D4204T13	D4204T16
Type	In-line, 4 cyl. turbocharged	In-line 4 cyl. turbo diesel	In-line 4 cyl. turbo diesel
Configuration	FWD	FWD	FWD
Displacement	1498 cm³	1969 cm³	1969 cm³
Bore	82,0 mm	82,0 mm	82,0 mm
Stroke	70,9 mm	93,2 mm	93,2 mm
Compression ratio	10,5:1	16,0:1	16,0:1
Valves, no/cylinder	4 ea.	4 ea.	4 ea.
DOHC / SOHC	DOHC	DOHC	DOHC
Engine management system	Gasoline direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection
Ignition sequence	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2
Engine idling speed	850 rpm ± 100	850 rpm ± 150	825 rpm ± 150
Fuel, rec. Octane	95 - 98 RON	Diesel ¹	Diesel ¹
Max engine speed	6000 rpm	4500 rpm	4500 rpm
Max output	112 kW (152 hp) / 5000 rpm	88 kW (120 hp) / 3750 rpm	110 kW (150 hp) / 3750 rpm
Max torque	250 / 28-67 Nm / rps	280 / 25-38 Nm / rps	320 / 29-50 Nm / rps
¹ According to EN590 Maximum biodiesel (FAME) content 7%			
Transmissions			
Transmissions	AW TG-71SC	M76 R7,0 / AW TF-71SC	M76 R7,0 / AW TF-71SC
First Gear	4,044	3,583 / 4,044	3,583 / 4,044
Second Gear	2,371	2,048 / 2,371	2,048 / 2,371
Third Gear	1,556	1,290 / 1,556	1,290 / 1,556
Fourth Gear	1,159	0,886 / 1,159	0,886 / 1,159
Fifth Gear	0,852	0,651 / 0,852	0,651 / 0,852
Sixth Gear	0,672	0,511 / 0,672	0,511 / 0,672
Reverse Gear	3,193	3,333 / 3,193	3,333 / 3,193
Manual Gearbox/final drive	-	4,056 (gear 1-6) - 4,563 (gear R)	4,056 (gear 1-6) - 4,563 (gear R)
Automatic Gearbox/final drive	3,365	3,365	3,365
Performance			
Performance	Automatic	Manual / Automatic	Manual / Automatic
Gearbox	AW TG-71SC	M76 R7,0 / AW TF-71SC	M76 R7,0 / AW TF-71SC
Acceleration, 0-100 km/h	8,5 sec	10,7 sec / 10,6 sec	8,7 sec / 8,6 sec
Top speed, km/h	210 km/h	190 km/h / 190 km/h	205 km/h / 205 km/h
Tyre class A Combined, NEDC*, l/100 km / CO² g/km ¹	- / 5,8 l/100 km / 134 g/km	4,7 l/100 km / 123 g/km / 4,6 l/100 km / 121 g/km	4,7 l/100 km / 123 g/km / 4,6 l/100 km / 121 g/km
Tyre class B Combined, NEDC*, l/100 km / CO² g/km ¹	- / 5,8 l/100 km / 136 g/km	4,8 l/100 km / 125 g/km / 4,7 l/100 km / 124 g/km	4,7 l/100 km / 125 g/km / 4,7 l/100 km / 124 g/km
Tyre class C Combined, NEDC*, l/100 km / CO² g/km ¹	- / 5,9 l/100 km / 138 g/km	4,8 l/100 km / 127 g/km / 4,8 l/100 km / 127 g/km	4,8 l/100 km / 127 g/km / 4,8 l/100 km / 127 g/km
Tyre class E Combined, NEDC*, l/100 km / CO² g/km ¹	- / 6,0 l/100 km / 140 g/km	4,9 l/100 km / 129 g/km / 5,0 l/100 km / 131 g/km	4,9 l/100 km / 129 g/km / 5,0 l/100 km / 131 g/km
Combined, WLTP (low-high)	6,8 - 7,6 / 156 - 173	5,0 - 5,6 / 131 - 148 // 5,3 - 5,9 / 141 - 155	5,0 - 5,6 / 133 - 147 // 5,3 - 5,9 / 141 - 155
¹ * NEDC figures correlated from WLTP based testing			
Measurements and Volumes			
Length	4370 mm	4370 mm	4370 mm
Width (Body width)	1783 mm	1783 mm	1783 mm
Width (Including mirrors, folded)	1857 mm	1857 mm	1857 mm
Width (Including mirrors, outer edge)	2041 mm	2041 mm	2041 mm
Height (Including shark fen)	1470 mm	1470 mm	1470 mm
Height (Excluding shark fen)	1458 mm	1458 mm	1458 mm
Wheelbase	2647 mm	2647 mm	2647 mm
Track, front (46 / 50 mm)	1552 mm / 1547 mm	1552 mm / 1547 mm	1552 mm / 1547 mm
Track, rear (46 / 50 mm)	1540 mm / 1535 mm	1540 mm / 1535 mm	1540 mm / 1535 mm
Ground clearance (Std / Sport chassis)	144 mm - 153 mm	144 mm - 153 mm	144 mm - 153 mm
Weight/Miscellaneous			
Weight (Depending on type of engine, gearbox etc.)	1460 kg - 1502 kg	1460 kg - 1502 kg	1460 kg - 1502 kg
Total Weight (Depending on type of engine, gearbox etc.)	1975 kg - 1995 kg	1975 kg - 1995 kg	1975 kg - 1995 kg
Max trailer weight, Unbraked (Max)	700 kg	700 kg	700 kg
Max trailer weight, Braked (Max)	1500 kg	1500 kg	1500 kg
Fuel tank, Petrol	62 l	-	-
Fuel tank, Diesel	-	62 l	62 l
Aerodynamics, (Cd)	0,32 - 0,34	0,32 - 0,34	0,32 - 0,34
Aerodynamics, (Frontal area)	2,2 m²	2,2 m²	2,2 m²
Max roof load	75 kg	75 kg	75 kg
SCR tank ¹	-	16,5 l	16,5 l
¹ = Market codes, D4204T13: 10, 14, 15, 19, 26, 49 / D4204T16: 10, 14, 15, 19, 26, 41, 48			
Interior Measurements			
Headroom with sunroof (front/rear)	948 mm / 922 mm	948 mm / 922 mm	948 mm / 922 mm
Headroom without sunroof (front/rear)	984 mm / 932 mm	984 mm / 932 mm	984 mm / 932 mm
Passenger compartment width at shoulder height (front/rear)	1396 mm / 1349 mm	1396 mm / 1349 mm	1396 mm / 1349 mm
Leg room (front/rear)	1073 mm / 847 mm	1073 mm / 847 mm	1073 mm / 847 mm
Hip room (front/rear)	1374 mm / 1352 mm	1374 mm / 1352 mm	1374 mm / 1352 mm
Cargo length from the second seatback to the tailgate measured at the height of the floor covering (std / opt)	684 mm / 782 mm	684 mm / 782 mm	684 mm / 782 mm
Cargo length from the first seatback to the tailgate measured at the height of the floor covering (std / opt)	1508 mm / 1545 mm	1508 mm / 1545 mm	1508 mm / 1545 mm
Cargo floor height to ground (std / opt)	553 mm / 655 mm	553 mm / 655 mm	553 mm / 655 mm
Rear opening height	532 mm	532 mm	532 mm
Cargo height (rear wheel center and car center line) (std / opt)	760 mm / 644 mm	760 mm / 644 mm	760 mm / 644 mm
Width of luggage compartment between wheelhouses	960 mm	960 mm	960 mm
Rear opening width at floor, min.	916 mm	916 mm	916 mm
Chassis			
Suspension front	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar
Suspension rear	Independent Suspension with Coil Springs, Hydraulic Monotube Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Monotube Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Monotube Shock Absorbers, Stabilizer Bar
Steering	Electrically Power Assisted Rack and Pinion Steering	Electrically Power Assisted Rack and Pinion Steering	Electrically Power Assisted Rack and Pinion Steering
Steering (angle/angle)	14,7	14,7	14,7
Turning circle (Curb to curb) (205/225)	10,9 m / 11,3 m	10,9 m / 11,3 m	10,9 m / 11,3 m
Turning circle (Wall to wall) (205/225)	11,2 m / 11,6 m	11,2 m / 11,6 m	11,2 m / 11,6 m
Turns of steering wheel end to end (205/225)	2,73 / 2,65	2,73 / 2,65	2,73 / 2,65
Braking system	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)
Brake disc diameter (front)	300 mm / 320 mm	300 mm / 320 mm	300 mm / 320 mm
Brake disc diameter (rear)	280 mm	280 mm	280 mm
Brake disc thickness (front)	25 mm	25 mm	25 mm
Brake disc thickness (rear)	11 mm	11 mm	11 mm
Braking distance 100-0 km/h	37 m	37 m	37 m