2012 Volvo V60 Specifications

	Petrol T3	Petrol T4	Ethanol/Petrol T4F	Petrol T5	Petrol T6	DRIVe	Diesel D3	Diesel D5	Diesel D5
Engine									
Engines	B4164T3	B4164T	B4164T2	B4204T7	B6304T4	D4162T	D5204T3	D5244T11	D5244T15
Type	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 6 cyl. Turbo	In-line 4 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel
Configuration	FWD	FWD	FWD	FWD	AWD	FWD	FWD	FWD	AWD
Displacement	1596 cm³	1596 cm³	1596 cm³	1999 cm³	2953 cm³	1560 cm³	1984 cm³	2400 cm³	2400 cm³
Bore	79.0 mm	79.0 mm	79.0 mm	87.5 mm	82.0 mm	75.0 mm	81.0 mm	81.0 mm	81.0 mm
Stroke	81.4 mm	81.4 mm	81.4 mm	83.1 mm	93.2 mm	88.3 mm	77.0 mm	93.15 mm	93.15 mm
Compression ratio	10.0:1	10.0:1	10.0:1	10.0:1	9.3:1	16.0:1	16.5:1	16.5:1	16.5:1
Valves, no/cylinder	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	2 ea.	4 ea.	4 ea.	4 ea.
DOHC / SOHC	DOHC	DOHC	DOHC	DOHC	DOHC	SOHC	DOHC	DOHC	DOHC
Engine management system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling
Ignition sequence	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 5 - 3 - 6 - 2 - 4	1 - 3 - 4 - 2	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3
Engine idling speed	750 rpm	750 rpm	750 rpm	780 rpm	590 rpm	790 rpm	700 rpm	740 rmn	700 auto
Fuel, rec. Octane	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	E85 is recommended (Mixture 15 % Petrol and 85 % Ethanol)	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48
Max output	115 kW (150 hp) / 5700 rpm	132 kW (180 hp) / 5700 rpm	132 kW (180 hp) / 5700 rpm	177 kW (240 hp) / 5500 rpm	224 kW (304 hp) / 5600 rpm	84 kW (115 hp) / 3600 rpm	120 kW (163 hp) / 3500 rpm	158 kW (215 hp) / 4000 rpm	158 kW (215 hp) / 4000 rpm
Max torque	240 / 27- 67 Nm / rps	240 (Overboost to 270) / 27- 83 Nm / rps	240 (Overboost to 270) / 27- 83 Nm / rps	320 / 30 - 83 Nm / rps	440 / 35 - 70 Nm / rps	270 / 29 - 42 Nm / rps	400 / 25 - 46 Nm / rps	420 / 25- 54 Nm / rps	440 / 25- 50 Nm / rps
Transmissions									
Transmissions	MMT6 W3 / MPS6-7	MMT6 Z3 / MPS6-7	MMT6 Z3 / MPS6-7	MMT6 Z3 / MPS6-7	-	MMT6 W3 / MPS6-7	M66K R1A / AW TF-80SC / AW TF-80SD	M66D R3A	AW TF-80SC (FWD) / AW TF-80SC (AWD)
First Gear	3,583 / 3,818	3,818 / 3,818	3,818 / 3,818	3,818 / 3,818	-	3,583 / 3,583	3,583 / 4,148 / 4,148	3.385	4.148
Second Gear	1,952 / 2,150	2,150 / 2,150	2,150 / 2,150	2,150 / 2,150	-	1,952 / 1,952	1,905 / 2,370 / 2,370	1.905	2.370
Third Gear	1,241 / 1,407	1,423 / 1,407	1,423 / 1,407	1,423 / 1,407	-	1,241 / 1,194	1,194 / 1,556 / 1,556	1.194	1.556
Fourth Gear	0,868 / 1,029	1,029 / 1,029	1,029 / 1,029	1,029 / 1,029	-	0,868 / 0,842	0,838 / 1,155 / 1,155	0.838	1.155
Fifth Gear	0,943 / 1,188	1,129 / 1,188	1,129 / 1,188	1,129 / 1,188	-	0,943 / 0,943	0,652 / 0,859 / 0,859	0.652	0.859
Sixth Gear	0,789 / 0,971	0,943 / 0,971	0,943 / 0,971	0,943 / 0,971	-	0,789 / 0,789	0,540 / 0,686 / 0,686	0.540	0.540
Reverse Gear	5,099 / 5,284	5,434 / 5,284	5,434 / 5,284	5,434 / 5,284	-	5,099 / 4,843	3,327 / 3,394 / 3,394	3.231	3.394
Manual Gearbox/final drive	3,813 (gear 1-4) - 2,773 (gear 5-6/R)	3,690 (gear 1-4) - 2,682 (gear 5-6/R)	3,690 (gear 1-4) - 2,682 (gear 5-6/R)	3,813 (gear 1-4) - 2,773 (gear 5-6/R)	-	4,063 (gear 1-4) - 2,955 (gear 5-6/R)	3.565	4.000	-
Automatic Gearbox/final drive	3,933 (gear 1-4) - 2,682 (gear 5-6/R)	3,933 (gear 1-4) - 2,682 (gear 5-6/R)	3,933 (gear 1-4) - 2,682 (gear 5-6/R)	3,933 (gear 1-4) - 2,682 (gear 5-6/R)	-	3,933 (gear 1-4) - 2,682 (gear 5-6/R)	3.075 / 3.075	-	3.200
Transmissions (AWD)	-	-	-	-	AW TF-80SC	-	-	-	AW TF-80SC
First Gear (AWD)	-	-	-	-	4.148	-	-	-	4.148
Second Gear (AWD)	-	-	-	-	2.370	-	-	-	2.370
Third Gear (AWD)	-	-	-	-	1.556	-	-	-	1.556
Fourth Gear (AWD)	-	-	-	-	1.155	-	-	-	1.155
Fifth Gear (AWD)	-	-	-	-	0.859	-	-	-	0.859
Sixth Gear (AWD)	-	-	-	-	0.686	-	-	-	0.686
Reverse Gear (AWD)	-	-	-	-	3.394	-	-	-	3.394
Manual Gearbox/final drive (AWD)	-	-	-	-	-	-	-	-	-
Automatic Gearbox / final drive (AWD)	-	-	-	-	3.329	-	-	-	3.329
Performance									
Performance	Manual / Automatic	Manual / Automatic	Manual / Automatic	Manual / Automatic	Automatic	Manual / Automatic	Manual / Automatic (No S/S) / Automatic (S/S)	Manual	Automatic / Automatic
Gearbox	MMT6 W3 / MPS6-7	MMT6 Z3 / MPS6-7	MMT6 Z3 / MPS6-7	MMT6 Z3 / MPS6-7	AW TF-80SC	MMT6 W3 / MPS6-7	M66K R1A / AW TF-80SC / AW TF-80SD	M66D R3A	AW TF-80SC (FWD) / AW TF-80SC (AWD)
Acceleration, 0-100 km/h	9.6 sec / 10.4 sec	8.5 sec / 9.2 sec	8.5 sec / 9.2 sec	7.5 sec / 7.7 sec	6.2 sec	11.3 sec / 12.7 sec	9.4 sec / 9.4 sec / 9.4 sec	7.5 sec	7.7 sec (FWD) / 7.7 sec (AWD)
Top speed, km/h	200 km/h / 205 km/h	220 km/h / 220 km/h	220 km/h / 220 km/h	230 km/h / 230 km/h	250 km/h	190 km/h / 185 km/h	220 km/h / 215 km/h (215 km/h	230km/h	230 km/h (FWD) / 225 km/h (AWD)
Fuel consumption (EC 199/100, Combined)	6.0 l/100km / 7.4 l/100km	6.6 l/100km / 7.4 l/100km	7.0 l/100km (petrol) (MMT6) - 7.5 l/100km (petrol) (MPS6-7) / 9.5 l/100km (E85) (MMT6) - 10.2 l/100km (E85) (MPS6-7)	8.1 l/100km / 8.3 l/100km	10.2 l/100km	4.5 l/100km / 4.5 l/100km	5.1 l/100km / 6.0 l/100km / 5.7 l/100km	4.9 l/100km	6.2 l/100km (FWD) / 6.4 l/100km (AWD)
CO^2	139 g/km / 171 g/km	153 g/km / 171 g/km	163g/km (petrol) / 156 g/km (E85) / 173g/km (petrol) / 167 g/km (E85)	189 g/km / 194 g/km	237 g/km	119 g/km / 119 g/km	132 g/km / 159 g/km / 149 g/km	129 g/km	162 g/km (FWD) / 169 g/km (AWD)
Measurements and Volumes									
Length	4628 mm	4628 mm	4628 mm	4628 mm	4628 mm	4628 mm	4628 mm	4628 mm	4628 mm
Width including mirrors, folded	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm
Width including mirrors, outer edge	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm
Height (including shark fin)	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm
Wheelbase (L110)	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm
Track, front (16"/17")	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm
Track, rear (16"/17")	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm
Ground clearance	136 mm	136 mm	136 mm	136 mm	-	136 mm	136 mm	136 mm	136 mm
Ground clearance, AWD	-	-	-	-	136 mm	-	-	-	136 mm
Serving Weight (Depending on type of engine, gearbox etc.)	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg	1526 kg / 1740 kg
Total Weight (Depending on type of engine, gearbox etc.)	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg	2100 kg / 2310 kg
Weight/Miscellaneous									
Max trailer weight, Unbraked (Max)	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg
Max trailer weight, Braked (Max)	1600 kg (man) / 1600 kg (auto)	1600 kg (man) / 1600 kg (auto)	1600 kg (man) / 1600 kg (auto)	1800 kg (man) / 1800 kg (auto)	1800 kg	1300 kg (man) / 1300 kg (auto)	1600 kg (man) / 1600 kg (auto)	1600 kg	1800 kg
Fuel tank, Petrol	67,5 l	67,5 l	-	67,5 l	67,5 l	-	-	-	-
Fuel tank, Diesel	-	-	-	-	-	67,5 l	67,5 l	67,5 l	67,5 l
Fuel tank, E85	-	-	67,5 l	-	-	-	-	-	-
Aerodynamics, (Cd)	0.29	0.29	0.29	0.29	0.29	0.28	0.29	0.29	0.29
Aerodynamics, (Frontal area)	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,27 m²	2,28 m²	2,28 m²	2,28 m²
Max roof load	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg
Interior Measurements									
Headroom with sunroof (front/rear)	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 951 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm
Headroom without sunroof (front/rear)	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm	973 mm / 954 mm
Passenger compartment width at shoulder height (front/rear)	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm
Leg room (front/rear)	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm
Hip room (front/rear)	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm
Cargo length from the second seatback to the tailgate measured at the top of the second seatback (SAE L224-2)	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm
Cargo length from the second seatback to the tailgate measured at the height of the floor covering (SAE L232-2)	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm
Cargo length from the first seatback to the tailgate measured at the top of the first seatback (SAE L224-1)	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm
Cargo length from the first seatback to the tailgate measured at the height of the floor covering (SAE L232-1)	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm
Rear opening height	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm
Rear opening height (car center line) (SAE H201)	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm
Luggage floor, height to ground	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm
Width of luggage compartment between wheelhouses	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm
Rear opening width upper, min. (GOE W205)	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm
Rear opening width maximum (GOE W206)	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm
Rear opening width at floor, min. (GOE W207)	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm
Chassis									
Suspension front	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar
Suspension rear	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Independent Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar
Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering	Power Assisted Rack and Pinion Steering
Steering (angle/angle)	15	15	15	15	15	15	15	15	15
Turning circle (Kerb to kerb)	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m	11,3 m / 11,9 m
Turning circle (Wall to wall) m	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4	11,5 / 12,4
Turns of steering wheel end to end	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58	2,7 / 2,58
Braking system	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)
Brake disc diameter (front)	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm	300 mm / 336 mm
Brake disc diameter (rear)	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm	302 mm
Brake disc thickness (front)	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm
Brake disc thickness (rear) (Solid EPDV/ventilated EPD)	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm	11 mm / 22 mm
Braking distance 100-0 km/h	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m	37 m