2015 Volvo V60 Specifications

	V60 T3 (150 hp) man/aut	V60 T4 (180 hp) man/aut	V60 T4F (180 hp) man/aut	V60 T5 (245 hp) aut	V60 T6 Polestar (306 hp) aut	V60 T6 AWD (304 hp) aut	V60 T6 AWD (350 hp) aut	V60 D2 (115 hp) man/aut	V60 D3 (136 hp) man/aut	V60 D4 (163 hp) man/aut (S/S)	V60 D4 AWD (163 hp) aut	V60 D4 (181 hp) man/aut	V60 D4 AWD (181 hp) aut	V60 D5 (215 hp) man	V60 D5 FWD/AWD (215 hp) aut	V60 Twin Engine D5 AWD (163 hp) aut	V60 Twin Engine D6 AWD (215 hp) aut
Engine																	
Engines	B416AT3	B416AT	B416AT2	B420AT11	B420AT9	B630AT4	B630AT5	D416ZT	D520AT7	D520AT3	D524AT17	D420AT5	D524AT12	D524AT11	D524AT11	DEPHEV	DEPHEV
Type	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 4 cyl. Turbo	In-line 6 cyl. Turbo	In-line 6 cyl. Turbo	In-line 4 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel	In-line 5 cyl. Turbodiesel
Configuration	FWD	FWD	FWD	FWD	FWD	AWD	AWD	FWD	FWD	FWD	AWD	FWD	AWD	AWD	FWD / AWD	AWD	AWD
Displacement	1596 cm³	1596 cm³	1596 cm³	1969 cm³	1969 cm³	2953 cm³	2953 cm³	1560 cm³	1984 cm³	1984 cm³	2400 cm³	1969 cm³	2400 cm³	2400 cm³	2400 cm³	2400 cm³	2400 cm³
Bore	79,0 mm	79,0 mm	79,0 mm	82,0 mm	82,0 mm	82,0 mm	82,0 mm	75,0 mm	81,0 mm	81,0 mm	81,0 mm	82,0 mm	81,0 mm	81,0 mm	81,0 mm	81,0 mm	81,0 mm
Stroke	81,4 mm	81,4 mm	81,4 mm	93,2 mm	93,2 mm	93,2 mm	93,2 mm	88,3 mm	77,0 mm	77,0 mm	93,2 mm	93,2 mm	93,2 mm	93,15 mm	93,15 mm	93,2 mm	93,15 mm
Compression ratio	10,0:1	10,0:1	10,0:1	10,8:1	10,8:1	9,3:1	9,3:1	16,0:1	16,5:1	16,5:1	16,5:1	15,8:1	16,5:1	16,5:1	16,5:1	16,5:1	16,5:1
Valves, no/cylinder	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	2 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.
DOHC / SOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	SOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC
Engine management system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Integrated fuel (SFI) / ignition control system	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling	Common rail electronic fuelling
Ignition sequence	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 5 - 3 - 6 - 2 - 4	1 - 5 - 3 - 6 - 2 - 4	1 - 3 - 4 - 2	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3	1 - 3 - 4 - 2	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3
Engine idling speed	750 rpm	750 rpm	750 rpm	675 - 950 rpm	675 - 950 rpm	590 rpm	590 rpm	750 rpm	700 rpm	700 rpm	700 rpm	625 rpm	700 rpm	700 rpm	740 rpm	700 rpm	800 rpm
Fuel, rec. Octane	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	E85 is recommended (Mixture 15 % Petrol and 85 % Ethanol)	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	For best performance and lowest fuel consumption 98 RON is recommended. For normal driving 95 RON can be used. 91 RON should only be used in exceptional cases.	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48	Diesel. Cetane Number min 48
Max engine speed	6150 rpm	6150 rpm	6150 rpm	6000 rpm	6000 rpm	6500 rpm	6500 rpm	5000 rpm	5000 rpm	5000 rpm	5200 rpm	5000 rpm	5200 rpm	5200 rpm	5200 rpm	5200 rpm	5200 rpm
Max output	110 kW (150 hp) / 5700 rpm	132 kW (180 hp) / 5700 rpm	132 kW (180 hp) / 5700 rpm	180 kW (245 hp) / 5500 rpm	225 kW (306 hp) / 5700 rpm	224 kW (304 hp) / 5800 rpm	258 kW (350 hp) / 5800 rpm	84 kW (115 hp) / 5000 rpm	100 kW (136 hp) / 5000 rpm	120 kW (163 hp) / 3500 rpm	120 kW (163 hp) / 4000 rpm	133 kW (181 hp) / 4000 rpm	133 kW (181 hp) / 4000 rpm	158 kW (215 hp) / 4000 rpm	158 kW (215 hp) / 4000 rpm	120 kW (163 hp) / 3500 rpm	158 kW (215 hp) / 3500 rpm
Max torque	240 / 27-67 Nm / rps	240 / 27-63 Nm/rps	240 / 27-63 Nm/rps	350 / 25-60 Nm/rps	400 / 35-75 Nm/rps	440 / 35-70 Nm / rps	500 / 50-79 Nm / rps	270 / 29-42 Nm / rps	350 / 25-38 Nm / rps	400 / 25-46 Nm / rps	420 / 25-42 Nm / rps	400 / 29-42 Nm/rps	420 / 25-42 Nm / rps	420 / 25-54 Nm / rps	440 / 25-50 Nm / rps	440 / 25 - 50 Nm / rps	440 / 25 - 50 Nm / rps
Battery type	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Lithium-ion battery	Lithium-ion battery
Battery content, useable energy (kWh)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	8 kWh	8 kWh
Battery content, total amount of energy (kWh)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	11,2 kWh	11,2 kWh
Battery charging time[**] - at 16A / 10A / 3A fuse (hours) [*]	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3,5 / 4,5 / 7,5	3,5 / 4,5 / 7,5
Battery placement	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Over rear axel, outside crash zone
Electrical motor max power (kW)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Cont.: 20 kW, Peak: 50 kW	Cont.: 20 kW, Peak: 50 kW
Electrical motor max torque (Nm)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Cont.: 105 Nm, Peak: 200 Nm	Cont.: 105 Nm, Peak: 200 Nm
Drivetime max power (kW)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50 kW + 120 kW[***]	50 kW + 158 kW[***]
Drivetime max torque (Nm)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	200 Nm + 420 Nm[***]	200 Nm + 440 Nm[***]

[*] ***= Time pending on e.g. ambient temp

[**] To "hybrid", "Power" and "EV_HOD" mode

Transmissions

Transmissions	MMT6 W3 FD 3,81 / MP56-7	MMT6 Z3 FD 3,69 / MP56-7	MMT6 Z3 FD 3,69 / MP56-7	AW TG-815C	AW TG-815C	-	-	-	MMT6 W3 FD 4,063 / MP56-4	M66D / AW TF-80SD	M66D / AW TF-80SD	-	M66F / AW TG-815C	-	M66D	AW TF-80SC	-
First Gear	3,583 / 3,818	3,818 / 3,818	3,818 / 3,818	5,250	5,250	-	-	-	3,583 / 3,583	3,385 / 4,148	3,385 / 4,148	-	3,583 / 4,148	-	3,385	4,148	-
Second Gear	1,952 / 2,150	2,150 / 2,150	2,150 / 2,150	3,029	3,029	-	-	-	1,952 / 1,952	1,905 / 2,370	1,905 / 2,370	-	2,050 / 2,370	-	1,905	2,370	-
Third Gear	1,241 / 1,407	1,423 / 1,407	1,423 / 1,407	1,950	1,950	-	-	-	1,241 / 1,194	1,194 / 1,556	1,194 / 1,556	-	1,267 / 1,556	-	1,194	1,556	-
Fourth Gear	0,868 / 1,029	1,029 / 1,029	1,029 / 1,029	1,457	1,457	-	-	-	0,868 / 0,842	0,838 / 1,155	0,838 / 1,155	-	0,838 / 1,155	-	0,838	1,155	-
Fifth Gear	0,943 / 1,166	1,129 / 1,166	1,129 / 1,166	1,221	1,221	-	-	-	0,943 / 0,943	0,652 / 0,859	0,652 / 0,859	-	0,617 / 0,859	-	0,652	0,859	-
Sixth Gear	0,789 / 0,971	0,943 / 0,971	0,943 / 0,971	1,000	1,000	-	-	-	0,789 / 0,789	0,540 / 0,686	0,540 / 0,686	-	0,510 / 0,686	-	0,540	0,686	-
Seventh Gear	-	-	-	0,809	0,809	-	-	-	-	-	-	-	-	-	-	-	-
Eighth Gear	-	-	-	0,673	0,673	-	-	-	-	-	-	-	-	-	-	-	-
Reverse Gear	5,099 / 5,284	5,434 / 5,284	5,434 / 5,284	4,015	4,015	-	-	-	5,099 / 4,843	3,200 / 3,394	3,200 / 3,394	-	2,833 / 3,394	-	3,200	3,394	-
Manual Gearbox/final drive	3,813 (gear 1-4) - 2,773 (gear 5-6=R)	3,690 (gear 1-4) - 2,662 (gear 5-6=R)	3,690 (gear 1-4) - 2,662 (gear 5-6=R)	2,774	2,774	-	-	-	4,063 (gear 1-4) - 2,955 (gear 5-6=R)	3,773	3,773	-	3,773	-	3,773	-	-
Automatic Gearbox/final drive	3,933 (gear 1-4) - 2,862 (gear 5-6=R)	3,933 (gear 1-4) - 2,862 (gear 5-6=R)	3,933 (gear 1-4) - 2,862 (gear 5-6=R)	-	-	-	-	-	3,933 (gear 1-4) - 2,862 (gear 5-6=R)	3,075	3,075	-	3,773 (gear 1-4) - 4,611 (gear R)	-	3,200	-	-
Transmissions (AWD)	-	-	-	-	-	AW TF-80SC	AW TF-80SC	-	-	-	-	AW TF-80SC	-	AW TF-80SC	-	AW TF-80SC	AW TF-80SC
First Gear (AWD)	-	-	-	-	-	4,148	4,148	-	-	-	-	4,148	-	4,148	-	4,148	4,148
Second Gear (AWD)	-	-	-	-	-	2,370	2,370	-	-	-	-	2,370	-	2,370	-	2,370	2,370
Third Gear (AWD)	-	-	-	-	-	1,556	1,556	-	-	-	-	1,556	-	1,556	-	1,556	1,556
Fourth Gear (AWD)	-	-	-	-	-	1,155	1,155	-	-	-	-	1,155	-	1,155	-	1,155	1,155
Fifth Gear (AWD)	-	-	-	-	-	0,859	0,859	-	-	-	-	0,859	-	0,859	-	0,859	0,859
Sixth Gear (AWD)	-	-	-	-	-	0,686	0,686	-	-	-	-	0,686	-	0,686	-	0,686	0,686
Reverse Gear (AWD)	-	-	-	-	-	3,394	3,394	-	-	-	-	3,394	-	3,394	-	3,394	3,394
Automatic Gearbox / final drive (AWD)	-	-	-	-	-	3,329	3,329	-	-	-	-	3,329	-	3,229	-	3,329	3,075

Performance

Performance	Manual / Automatic	Manual / Automatic	Manual / Automatic	Automatic	Automatic	Automatic	Automatic	Manual / Automatic	Manual / Automatic	Manual / Automatic (S/S)	Automatic	Manual / Automatic	Automatic	Manual	Automatic / Automatic	Automatic	Automatic
Gearbox	MMT6 W3 FD 3,81 / MP56-7	MMT6 Z3 FD 3,69 / MP56-7	MMT6 Z3 FD 3,69 / MP56-7	AW TG-815C	AW TG-815C	AW TF-80SC	AW TF-80SC	MMT6 W3 FD 4,063 / MP56-4	M66D / AW TF-80SD	M66D / AW TF-80SD	AW TF-80SC	M66F / AW TG-815C	AW TG-815C	M66D	AW TF-80SC (FWD) / AW TF-80SC (AWD)	AW TF-80SC	AW TF-80SC
Acceleration, 0-100 km/h	9,6 sec / 10,4 sec	8,5 sec / 9,2 sec	8,5 sec / 9,2 sec	6,4 sec	6,0 sec	6,0 sec	5,0 sec	11,3 sec / 12,7 sec	10,4 sec / 10,4 sec	9,4 sec / 8,4 sec	10,4 sec	7,6 sec / 7,6 sec	8,8 sec	7,5 sec	7,7 sec (FWD) / 7,7 sec (AWD)	5,0 sec (Hybrid-mode) / - (Pure-mode) / 6,1 sec (Power-mode) / - (EL-AWD-mode)	7,3 sec (Hybrid-mode) / - (Pure-mode) / 6,1 sec (Power-mode) / - (EL-AWD-mode)
Top speed, km/h	200 km/h / 205 km/h	220 km/h / 220 km/h	220 km/h / 220 km/h	230 km/h	230 km/h	250 km/h	250 km/h	190 km/h / 185 km/h	205 km/h / 200 km/h	220 km/h / 215 km/h	215 km/h	225 km/h / 225 km/h	220 km/h	230 km/h	230 km/h (FWD) / 225 km/h (AWD)	120*210 (Hybrid-mode) / 125 km/h (Pure-mode) / 230 km/h (Power-mode) / 150 km/h (EL-AWD-mode) [1]	120*230 (Hybrid-mode) / 125 km/h (Pure-mode) / 230 km/h (Power-mode) / 150 km/h (EL-AWD-mode) [1]
Fuel consumption (EC 199/100, Combined)	5,8 l/100km / 7,2 l/100km	5,9 l/100km / 7,2 l/100km	7,0 l/100km (petrol) (MMT6) - 7,2 l/100km (petrol) (AW TF-80SC) - 2,1 l/100km (E85) (MMT6) - 8,8 l/100km (E85) (AW TF-80SC)	6,2 l/100km (6,1 l/100km[1])	6,7 l/100km	10,2 l/100km	10,2 l/100km	4,5 l/100km (4,1 l/100km[1]) / 4,6 l/100km (4,2 l/100km[1])	4,5 l/100km / 4,9 l/100km	4,5 l/100km / 4,9 l/100km	5,9 l/100km	3,9 l/100km (3,8 l/100km[1]) / 4,3 l/100km (4,2 l/100km[1])[2]	5,9 l/100km	4,8 l/100km	6,2 l/100km (FWD) / 5,9 l/100km (AWD)	1,8 (Hybrid-mode) / 0 (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)	1,8 (Hybrid-mode) / 0 (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)
CO[*]	134 g/km / 167 g/km	138 g/km / 167 g/km	162 g/km (petrol) (MMT6) - 2 g/km (E85)(MMT6) - 163g/km (petrol) (MP56-7) / 61 g/km (E85)(MP56-7)	144 g/km (142 g/km)[1]	157 g/km	237 g/km	237 g/km	119 g/km (108 g/km [1]) / 119 g/km (110 g/km [1])	119 g/km / 129 g/km	119 g/km / 129 g/km	158 g/km	105 g/km (99 g/km [1]) / 112g/km (109 g/km [1])	158 g/km	120 g/km	162 g/km (FWD) / 158 g/km (AWD)	46 g/km (Hybrid-mode) / 0 g/km (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)	46 g/km (Hybrid-mode) / 0 g/km (Pure-mode) / - (Power-mode) / - (EL-AWD-mode) [1]
Range	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	900 km (Hybrid-mode) / 50 km [**] (Pure-mode) / - (Power-mode) / - (EL-AWD-mode) [1]	900 km (Hybrid-mode) / 50 km [**] (Pure-mode) / - (Power-mode) / - (EL-AWD-mode) [1]

[1] = Electrical motor only

[2] = Restricted offer

[*] = Up to

Measurements and Volumes

Length	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm
Width (including mirrors, folded)	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm
Width (including mirrors, outer edge)	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm
Height (including shark fin)	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm
Wheelbase (L110)	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm
Track, front (16"/17")	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm
Track, rear (16"/17")	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm
Ground clearance	136 mm	136 mm	136 mm	136 mm	136 mm	-	-	136 mm	136 mm	136 mm	-	136 mm	-	136 mm	136 mm / -	-	-
Ground clearance, AWD	-	-	-	-	-	136 mm	136 mm	-	-	-	136 mm	-	136 mm	-	- / 136 mm	137 mm	137 mm

Weight/Miscellaneous

Serving Weight (Depending on type of engine, gearbox etc.)	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	1623 kg - 1834 kg	2058 kg - 2058 kg
Total Weight (Depending on type of engine, gearbox etc.)	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2100 kg - 2310 kg	2505 kg - 2505 kg
Max trailer weight, Unbraked (Max)	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	0 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg
Max trailer weight, Braked (Max)	1600 kg	1600 kg	1600 kg	1600 kg	1600 kg	1800 kg	0 kg	1300 kg	1600 kg	1600 kg	1800 kg	1750 kg	1800 kg	1800 kg	1800 kg	1800 kg	1800 kg
Fuel tank, Petrol	67,5 l	67,5 l	-	67,5 l	67,5 l	67,5 l	67,5 l	-	-	-	-	-	-	-	-	-	-
Fuel tank, Diesel	-	-	-	-	-	-	-	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	45,0 l	45,0 l
Fuel tank, E85	-	-	67,5 l	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Aerodynamics, (Cd)	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29
Aerodynamics, (Frontal area)	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²
Max roof load	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg

Interior Measurements

Headroom with sunroof (Frontmost)	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm
Headroom without sunroof (Frontmost)	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm
Passenger compartment width at shoulder height (frontmost)	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm
Leg room (frontmost)	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm
Hip room (frontmost)	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm
Cargo length from the second seatback to the tailgate measured at the top of the second seatback (SAE L224-2)	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm
Cargo length from the second seatback to the tailgate measured at the floor covering (SAE L202-2)	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm
Cargo length from the first seatback to the tailgate measured at the top of the first seatback (SAE Chart 1)	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm
Cargo length from the first seatback to the tailgate measured at the floor covering (SAE L202-1)	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm
Rear opening height	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	592 mm	592 mm
Cargo height (rear wheel center and rear seat back) (SAE n221)	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	675 mm	675 mm
Luggage floor, height to ground	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm
Width of luggage compartment between wheelhouses	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm
Rear opening width upper, min (ISCE W205)	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm
Rear opening width maximum (ISCE W206)	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm
Rear opening diameter (from, (ISCE W207)	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm
Suspension front	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar