2018 Volvo V60 Specifications

	V60 T2 (122 hp) aut	V60 T3 (152 hp) man	V60 T3 (152 hp) aut	V60 T4 (190 hp) man/aut	V60 T5 (245 hp) aut	V60 T6 FWD/AWD (306 hp) aut	V60 Polestar AWD (367 hp) aut	V60 D2 (120 hp) man	V60 D2 (120 hp) aut	V60 D3 (150 hp) man/aut	V60 D4 (190 hp) man/aut	V60 D4 AWD (190 hp) aut	V60 D5 (225 hp) aut	V60 D5 AWD (163 hp) aut	V60 D6 AWD (220 hp) aut
Engine															
Engines	B415ATS	B420ST37	B415ATT4	B420ST19	B420ST11	B420ST9	B420ST43	D420ST8	D420ST20	D420ST9	D420ST14	D520ST21	D420ST11	D87PHEV	D87PHEV
Type	In-line, 4 cyl, turbocharged	In-line, 4 cyl, turbocharged	In-line, 4 cyl, turbocharged	In-line, 4 cyl, turbocharged	In-line, 4 cyl, turbocharged	In-line 4 cyl, supercharged and turbocharged	In-line 4 cyl, supercharged and turbocharged	In-line 4 cyl, turbo diesel	In-line 4 cyl, turbo diesel	In-line 4 cyl, turbo diesel	In-line 4 cyl, twin turbo diesel	In-line 5 cyl, twin turbo diesel	In-line 4 cyl, twin turbo diesel	In-line 5 cyl, twin turbo diesel	In-line 5 cyl, twin turbo diesel
Configuration	FWD	FWD	FWD	FWD	FWD	FWD/AWD	AWD	FWD	FWD	FWD	FWD	AWD	FWD	AWD	AWD
Displacement	1498 cm³	1969 cm³	1498 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	1969 cm³	2400 cm³	1969 cm³	2400 cm³	2400 cm³
Bore	82.0 mm	82.0 mm	82.0 mm	82.0 mm	82.3 mm	82.5 mm	82.0 mm	82.0 mm	82.0 mm	82.0 mm	82.0 mm	81.0 mm	82.0 mm	81.0 mm	81.0 mm
Stroke	70.9 mm	93.2 mm	70.9 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm	93.2 mm
Compression ratio	10.5:1	11.3:1	10.5:1	11.3:1	10.8:1	10.3:1	8.6:1	16.0:1	16.0:1	16.0:1	15.8:1	16.5:1	15.8:1	16.5:1	16.5:1
Valves, no/cylinder	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.	4 ea.
DOHC / SOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC	DOHC
Engine management system	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Electronically controlled common rail direct injection	Common rail electronic fuelling	Common rail electronic fuelling
Ignition sequence	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 2 - 4 - 5 - 3	1 - 3 - 4 - 2	1 - 2 - 4 - 5 - 3	1 - 2 - 4 - 5 - 3
Driving speed	850 rpm a 100	850 rpm a 100	850 rpm a 100	850 rpm a 100	850 rpm a 100	850 rpm a 100	850 rpm a 100	850 rpm a 100	850 rpm a 100	825 rpm a 150	825 rpm a 150	825 rpm a 150	740 rpm a 25	825 rpm a 150	750 a 25 rpm
Fuel, rec. Octane	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]	Diesel [1]
Max engine speed	6000 rpm	6000 rpm	6000 rpm	6000 rpm	6000 rpm	6000 rpm	7000 rpm	4500 rpm	4500 rpm	4500 rpm	4500 rpm	5000 rpm	5200 rpm	5000 rpm	5200 rpm
Max output	90 kW (122 hp) / 5000 rpm	112 kW (152 hp) / 5000 rpm	112 kW (152 hp) / 5000 rpm	140 kW (190 hp) / 4700 rpm	180 kW (245 hp) / 5500 rpm	225 kW (306 hp) / 5700 rpm	270 kW (367 hp) / 6000 rpm	88 kW (120 hp) / 3750 rpm	88 kW (120 hp) / 3750 rpm	110 kW (150 hp) / 3750 rpm	140 kW (190 hp) / 4250 rpm	140 kW (190 hp) / 4000 rpm	165 kW (225 hp) / 4250 rpm	120 kW (163 hp) / 4000 rpm	162 kW (220 hp) / 4250 rpm
Max torque	220 / 27-58 Nm / rps	250 / 22-67 Nm / rps	250 / 28-67 Nm / rps	300 / 22-67 Nm / rps	350 / 25-80 Nm / rps	400 / 35-75 Nm / rps	470 / 52-85 Nm / rps	280 / 25-38 Nm / rps	280 / 25-38 Nm / rps	320 / 28-50 Nm / rps	400 / 29-42 Nm / rps	440 / 25-46 Nm / rps	470 / 29-42 Nm / rps	420 / 25 - 42 Nm / rps	440 / 25 - 50 Nm / rps
Battery type	-	-	-	-	-	-	-	-	-	-	-	-	-	Lithium-ion battery	Lithium-ion battery
Battery content, usable energy (kWh)	-	-	-	-	-	-	-	-	-	-	-	-	-	8 kWh	8 kWh
Battery content, total amount of energy (kWh)	-	-	-	-	-	-	-	-	-	-	-	-	-	11.2 kWh	11.2 kWh
Battery charging time[2] , at 16A / 10A / 5A fuse (hours) [3]	-	-	-	-	-	-	-	-	-	-	-	-	-	3.5 / 4.5 / 7.5	3.5 / 4.5 / 7.5
Battery placement	-	-	-	-	-	-	-	-	-	-	-	-	-	Over rear axel, outside crash zone	Over rear axel, outside crash zone
Electrical motor max power (kW)	-	-	-	-	-	-	-	-	-	-	-	-	-	50 kW	50 kW
Electrical motor max torque (Nm)	-	-	-	-	-	-	-	-	-	-	-	-	-	200 Nm	200 Nm
Drivetrine max power (kW)	-	-	-	-	-	-	-	-	-	-	-	-	-	50 kW + 120 kW [4]	50 kW + 162 kW [4]
Drivetrine max torque (Nm)	-	-	-	-	-	-	-	-	-	-	-	-	-	200 Nm + 420 Nm [4]	200 Nm + 440 Nm [4]

[1] According to ISO98 Maximum biodiesel (FAME) content 7%

[2] Battery

[3] In "Hybrid", "Power" and "EL-4WD" mode

Transmissions

Transmissions	AW TF-71SC	M66H	AW TF-71SC	M66H / AW TF-71SC	AW TG-81SC	AW TG-81SC	-	M66F	AW TF-71SC	M66F / AW TF-71SC	M66F / AW TG-81SC	-	AW TG-81SC	-	-
First Gear	4.044	3.385	4.044	3.385 / 4.044	5.250	5.250	-	3.583	4.044	3.583 / 5.250	3.583 / 5.250	-	5.250	-	-
Second Gear	2.371	1.952	2.371	1.952 / 2.371	3.029	3.029	-	2.050	2.371	2.050 / 2.371	2.050 / 3.029	-	3.029	-	-
Third Gear	1.556	1.267	1.556	1.267 / 1.556	1.950	1.950	-	1.267	1.556	1.267 / 1.556	1.267 / 1.950	-	1.950	-	-
Fourth Gear	1.159	0.868	1.159	0.868 / 1.159	1.457	1.457	-	0.838	1.159	0.838 / 1.159	0.838 / 1.457	-	1.457	-	-
Fifth Gear	0.852	0.652	0.852	0.652 / 0.852	1.221	1.221	-	0.617	0.852	0.617 / 0.852	0.617 / 1.221	-	1.221	-	-
Sixth Gear	0.672	0.540	0.672	0.540 / 0.672	1.000	1.000	-	0.510	0.672	0.510 / 0.672	0.510 / 1.000	-	1.000	-	-
Seventh Gear	-	-	-	-	0.809	0.809	-	-	-	-	- / 0.809	-	0.809	-	-
Eighth Gear	-	-	-	-	0.673	0.673	-	-	-	-	- / 0.673	-	0.673	-	-
Reverse Gear	3.193	2.692	3.193	2.692 / 3.193	4.015	4.015	-	2.833	3.193	2.833 / 3.193	2.833 / 4.015	-	4.015	-	-
Manual Gearbox/final drive	-	4.267 (gear 1-6) - 5.333 (gear R)	-	4.267 (gear 1-6) - 5.333 (gear R)	-	-	-	4.000 (gear 1-6) - 4.941 (gear R)	-	4.000 (gear 1-6) - 4.941 (gear R)	3.773 (gear 1-6) - 4.611 (gear R)	-	-	-	-
Automatic Gearbox/final drive	3.365	-	3.365	3.365	2.774	2.774	-	-	3.365	3.365	2.666	-	2.666	-	-
Transmissions (AWD)	-	-	-	-	-	AW TG-81SC	AW TG-81SC	-	-	-	-	AW TF-80SC	-	AW TF-80SC	AW TF-80SC
First Gear (AWD)	-	-	-	-	-	5.250	5.250	-	-	-	-	4.148	-	4.148	4.148
Second Gear (AWD)	-	-	-	-	-	3.029	3.029	-	-	-	-	2.370	-	2.370	2.370
Third Gear (AWD)	-	-	-	-	-	1.950	1.950	-	-	-	-	1.556	-	1.556	1.556
Fourth Gear (AWD)	-	-	-	-	-	1.457	1.457	-	-	-	-	1.155	-	1.155	1.155
Fifth Gear (AWD)	-	-	-	-	-	1.221	1.221	-	-	-	-	0.859	-	0.859	0.859
Sixth Gear (AWD)	-	-	-	-	-	1.000	1.000	-	-	-	-	0.686	-	0.686	0.686
Seventh Gear (AWD)	-	-	-	-	-	0.809	0.809	-	-	-	-	-	-	-	-
Eighth Gear (AWD)	-	-	-	-	-	0.673	0.673	-	-	-	-	-	-	-	-
Reverse Gear (AWD)	-	-	-	-	-	4.015	4.015	-	-	-	-	3.394	-	3.394	3.394
Automatic Gearbox / final drive (AWD)	-	-	-	-	-	3.075	3.329	-	-	-	-	3.075	-	3.075	3.075

Performance

Performance	Automatic	Manual	Automatic	Manual / Automatic	Automatic	Automatic / Automatic	Automatic	Manual	Automatic	Manual / Automatic	Manual / Automatic	Automatic	Automatic	Automatic	Automatic
Gearbox	AW TF-71SC	M66H	AW TF-71SC	M66H / AW TF-71SC	AW TG-81SC	AW TG-81SC / AW TG-81SC	AW TG-81SC	M66F	AW TF-71SC	M66F / AW TF-71SC	M66F / AW TG-81SC	AW TF-80SC	AW TG-81SC	AW TF-80SC	AW TF-80SC
Acceleration, 0-100 km/h	10,3 sec	8,7 sec	8,7 sec	7,3 sec / 7,3 sec	6,4 sec	6,0 sec / 6,0 sec	4,8 sec	11,5 sec	11,7 sec	9,1 sec / 9,1 sec	7,7 sec / 7,7 sec	8,9 sec	6,5 sec	9,0 sec (Hybrid-mode) / (Pure-mode) / 6,9 sec (Power-mode) / - (EL-AWD-mode)	7,9 sec (Hybrid-mode) / (Pure-mode) / 6,0 sec (Power-mode) / - (EL-AWD-mode)
Top speed	190 km/h	205 km/h	205 km/h	225 km/h / 225 km/h	230 km/h	230 km/h / 250 km/h	250 km/h	195 km/h	195 km/h	210 km/h / 210 km/h	225 km/h / 225 km/h	225 km/h	230 km/h	126*125 (Hybrid-modes) / 125 km/h (Pure-mode) / 210 km/h (Power-mode) / 150 km/h (EL-AWD-mode) [1]	126*125 (Hybrid-modes) / 125 km/h (Pure-mode) / 230 km/h (Power-mode) / 150 km/h (EL-AWD-mode) [1]
Fuel consumption (EC Directive, Combined)	5,9 l/100km	5,8 l/100km	5,9 l/100km	5,8 l/100km / 5,8 l/100km	6,4 l/100km	6,7 l/100km / 7,0 l/100km	8,1 l/100km	3,9 l/100km (3,8 l/100km) [2]	4,3 l/100km (4,2 l/100km) [2]	4,1 l/100km (4,0 l/100km) / 4,2 l/100km (4,2 l/100km) [2]	4,0 l/100km (3,8 l/100km) / 4,4 l/100km (4,3 l/100km) [2]	5,5 l/100km	4,8 l/100km	1,8 (Hybrid-mode) / 9 (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)	1,8 (Hybrid-mode) / 9 (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)
CO*	138 g/km	135 g/km	138 g/km	135 g/km / 136 g/km	149 g/km	157 g/km / 163 g/km	186 g/km	104 g/km (101 g/km*) [2]	114 g/km (111 g/km*) [2]	108 g/km (105 g/km*) / 114 g/km (111 g/km*) [2]	104 g/km (101 g/km*) / 118 g/km (112 g/km*) [2]	146 g/km	125 g/km	48 g/km (Hybrid-mode) / 0 g/km (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)	48 g/km (Hybrid-mode) / 0 g/km (Pure-mode) / - (Power-mode) / - (EL-AWD-mode)
Range	-	-	-	-	-	-	-	-	-	-	-	-	-	900 km (Hybrid-mode) / 50 km (Pure-mode) / - (Power-mode) / - (EL-AWD-mode) [3]	900 km (Hybrid-mode) / 50 km (Pure-mode) / - (Power-mode) / - (EL-AWD-mode) [3]

[1] * Electrical motor only

[2] * = Restricted offer

[3] * = Up to

Measurements and Volumes

Length	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4668 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm	4635 mm
Width (body only)	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm	1825 mm
Width (including mirrors, folded)	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm	1899 mm
Width (including mirrors, outer edge)	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm	2097 mm
Height (including shark fin)	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm	1484 mm
Wheelbase	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm	2776 mm
Track, front (16"/17")	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm	1588 mm / 1578 mm
Track, rear (16"/17")	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm	1585 mm / 1575 mm
Ground clearance	136 mm	136 mm	136 mm	136 mm	136 mm	136 mm	-	136 mm	136 mm	136 mm	136 mm	-	136 mm	-	-
Ground clearance, AWD	-	-	-	-	-	136 mm	136 mm	-	-	-	-	136 mm	-	137 mm	137 mm

Weight/Miscellaneous

Weight (Depending on type of engine, gearbox etc.)	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1990 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1980 kg	1557 kg - 1990 kg
Total Weight (Depending on type of engine, gearbox etc.)	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2270 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2130 kg - 2280 kg	2505 kg	2505 kg
Max trailer weight, Unbraked (MAU)	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	-	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg	750 kg
Max trailer weight, Braked (MAB)	1500 kg	1600 kg	1500 kg	1600 kg / 1600 kg	1800 kg	1800 kg / 1800 kg	-	1600 kg	1600 kg	1600 kg / 1600 kg	1800 kg / 1800 kg	1800 kg	1800 kg	1800 kg	1800 kg
Fuel tank, Petrol	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	-	-	-	-	-	-	-	-
Fuel tank, Diesel	-	-	-	-	-	-	-	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	67,5 l	45,5 l	45,0 l
Aerodynamics, (Cd)	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29
Aerodynamics, (frontal area)	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²	2,28 m²
Max roof load	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg	75 kg

Interior Measurements

Headroom without sunroof (frontmax)	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm	955 mm / 954 mm
Headroom without sunroof maximum (frontmax)	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm	999 mm / 954 mm
Passenger compartment width at shoulder height (frontmax)	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm	1447 mm / 1402 mm
Leg room (frontmax)	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm	1064 mm / 850 mm
Hip room (frontmax)	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm	1395 mm / 1349 mm
Cargo length from the second seatback to the tailgate measured at the top of the floor covering (SAE 1202-2)	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm	748 mm
Cargo length from the second seatback to the tailgate measured at the height of the floor covering (SAE 1202-2)	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm	978 mm
Cargo length from the first seatback to the tailgate measured at the top of the first seatback (SAE 1204-1)	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm
Cargo length from the first seatback to the tailgate measured at the height of the floor covering (SAE 1204-1)	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm	1749 mm
Rear opening height	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	658 mm	592 mm	592 mm
Rear opening height (car center line) (SAE H201)	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	742 mm	675 mm	675 mm
Luggage floor, height to ground	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm	646 mm
Width of luggage compartment between wheelhouses	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm	1090 mm
Rear opening width-upper, min (ISO/E W205)	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm	923 mm
Rear opening width-maximum (ISO/E W206)	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm	1095 mm
Rear opening width at floor, min (ISO/E W207)	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm	1082 mm

Chassis

Suspension front	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	MacPherson Strut, Polestar Coil Springs, Öhlins Shock Absorbers, Stabilizer Bar	MacPherson Strut, Coil Springs, Hydraulic