

ENGINES

Type
Configuration
Displacement, cm ³
Bore/Stroke (mm)
Engine cylinder block material
Cylinderhead material
Combustion chamber type
Compression ratio
Valves, no/cylinder
Camshafts
Engine management system
Ignition sequence
Engine idling speed
Fuel, rec. octane
Max output, hp/rpm.
Max torque, lb.-ft./rpm.


POWER AND TORQUE →

Manual gearbox/final drive
Automatic gearbox/final drive

PERFORMANCE


Gearbox
Acceleration, 0-62 mph (sec)
Top speed, mph
Fuel consumption, mpg

V8
8-cylinder naturally aspirated
Transverse, all wheel drive
4414
94/79.5
Aluminium
Aluminium
Pent-roof
10.4:1
4
4
Microprocessor controlled fuel and ignition system with self diagnostics
1-8-4-3-6-5-7-2
675
91-98 RON
311/5950
325/3950



AWTF-80SC/3.33
Automatic
6.5
130
TDB

I6
In-line, 6-cylinder naturally aspirated
Transverse, front wheel drive
3192
84/96
Aluminium
Aluminium
Pent-roof
10.8:1
4
2
Microprocessor controlled fuel and ignition system with self diagnostics
1-5-3-6-2-4
650
91-98 RON
235/6200
236/3200



AWTF-80SC/3.33
Automatic
8.0
130
TDB

MEASUREMENTS AND VOLUMES

EXTERIOR MEASUREMENTS (IN)	
Length	191
Width	73
Height	59
Wheelbase	112
Track, front	63/62 ^A
Track, rear	62/62 ^A
Ground clearance	6/5.5 ^B
Load height	27
WEIGHTS/MISCELLANEOUS	
Curb-weight, lb min.	3486-3839 ^B
Fuel tank, l	18.5
Max. trailer weight, lb	3968 ^C /4409 ^B
Drag coefficient	0.29

INTERIOR MEASUREMENTS (IN)	
Headroom with sunroof (front/rear)	38/38
Headroom without sunroof (front/rear)	39/38
Passenger compartment width at shoulder height (front/rear)	58/56
Luggage volume, ft ³ (DIN V210)	17
Load length	44
Load length with rear seat folded down	77
Loading height between cargo floor and parcel shelf	18
Width of luggage compartment between wheel arches	43

CHASSIS

Suspension	front	Spring-strut, lower link, anti-roll bar
	rear	Individual, Multi-Link, with coil springs, anti-roll bar
Steering		Rack and pinion, power assisted
Turning circle		36 ft / 40 ft ^P
Turns of steering wheel lock to lock		2.8 / 2.6 ^P
Braking system		ABS system with EBD.
		Ventilated discs
Brake disc diameter (front/rear)		12-13 in / 12 in

DSTC (Dynamic Stability Traction Control) Standard

TRANSMISSIONS

6-speed adaptive automatic geartronic transmission, electronically controlled, with lock-up and winter mode selection.

RATIO	AWTF-80SC
First	4.15
Second	2.37
Third	1.56
Fourth	1.16
Fifth	0.86
Sixth	0.69
Reverse	3.39

^A17" Wheels ^BV8 ^C16 ^PTires width 245