

Section 7 Suspension, damping, wheels**Group 77 Wheels, tyres, hubs****Wheel**

	Wheel with aluminium rim	Wheel with steel rim
Dimensions	6.5Jx15x43 6.5Jx16x43 7Jx16x49 7.5Jx17x49 8Jx17x46 8Jx18x46	6.5Jx15x43 6.5Jx16x43 7Jx16x49
Lateral runout, max.	0.4 mm (0.016")	0.8 mm (0.031")
Radial runout, maximum	0.4 mm (0.016")	0.7 mm (0.028")

Tightening torques

Wheel studs	140 Nm (103 lbf ft.)
-------------------	----------------------

Tyre dimensions

195/65 R 15
205/65 R 15
205/55 R 16
215/55 R 16
215/65 R 16
225/45 R 17
235/45 R 17
235/40 R 18
T125/80 R 17
T135/90R17
T115/85R18

Air pressure

Air pressure applies to cold tyres: kPa (psi)					
Model:	Speed km/h (mph)	1-3 people		Full load	
		Front	Rear	Front	Rear
V70 XC AWD	0 - 160 (0 - 100)	210 (30)	210 (31)	240 (34)	260 (38)
V70 XC AWD	High speed driving: 160-	220(32)	240(34)	280(41)	300(43)
"T-spare" T135/80 R 17	0 - 80 (0 - 50)	420 (61)	420 (61)	420 (61)	420 (61)
V70 AWD, TDI	0 -160 (0 - 100)	220 (32)	210 (31)	260 (38)	260 (38)
V70 AWD TDI	High speed driving: > 160 (> 100)	250 (36)	250 (36)	280 (41)	280 (41)
V70	High speed driving: > 160 (> 100)	250 (36)	250 (36)	280 (41)	280 (41)
V70	0 - 160 (0-100)	220 (32)	210 (31)	260 (38)	260 (38)
V70 Turbo	0-160 (0-100)	220(32)	210 (31)	260(38)	260(38)
V70 Turbo	High speed driving: > 160 (> 100)	250(36)	250(36)	280(41)	280(41)
V70 - R	0 - 250 0 - 155	240(34)	240(34)	270 (39)	270 (39)
"T-spare" T125/80 R 17	0 - 80 (0 - 50)	420 (61)	420 (61)	420 (61)	420 (61)