

# Section 7. Springs, shock absorbers, wheels

## Group 77 Wheels, tyres, hubs

### Wheels

Rims	Alu. rim	Steel rim
Dimension .....	6.5Jx15x43	6Jx15x43
Lateral runout.....max	0.6	0.8
Radial runout.....max	0.6	1.0

Tyre pressures, cold, kPa (psi)					
Tyre size	km/h	1 - 3 passengers (comfort)		Full load (economy)	
		Front	Rear	Front	Rear
<b>854:</b>	0 – 160	220 (32)	200 (29)	230 (33)36*	250 (36)
185/65H R15 195/60V R15 205/55V R15	160 –	250 (36)	250 (36)	250 (36)	280 (41)
<b>854 turbo:</b>	0 – 160	230 (33)34*	210 (30)31*	250 (36)	250 (36)
205/50Z R16	160 –	280 (41)	260 (38)	290 (42)	290 (42)
<b>855:</b>	0 – 160	220 (32)	210 (30)31*	240 (35)36*	280 (41)
185/65H R15 195/60V R15 205/55V R15	160 –	250 (36)	250 (36)	260 (38)	310 (45)
<b>855 turbo:</b>	0 – 160	230 (33)34*	220 (32)	250 (36)	280 (41)
205/50Z R16	160 –	280 (41)	270 (39)	290 (42)	320 (46)
Spare wheel 'Temporary spare'	0 – 80	420 (60)	420 (60)	420 (60)	420 (60)

\* For certain markets (psi). Check with owners manual.

### Tightening torque

	Nm	ft.lb
Wheel .....	110	81