

Section 7 Suspension, damping, wheels

Group 77 Wheels, tyres, hubs

Wheel

Dimension	Wheel with aluminium rim	Wheel with steel rim
		6.5Jx15x43 6.5Jx16x43 7Jx16x49 7.5Jx17x49
Lateral runout, max.	0.4 mm (0.016")	0.8 mm (0.031")
Radial runout, maximum	0.4 mm (0.016")	0.7 mm (0.028")

Tightening torques

Wheel studs	140 Nm (103 lbf ft.)
-------------------	----------------------

Tyre dimensions

195/65 R 15
205/55 R 16
215/55 R 16
215/65 R 16
225/45 R 17
T125/80 R 17

Air pressure

Air pressure applies to cold tyres: kPa (psi)					
Tyre size:	Vehicle speed km/h (mph)	1-3 people		Full load	
		Front	Rear	Front	Rear
S60 B5244S B5244S2	0 -160 (0 - 100)	200 (29)	200 (29)	260 (38)	260 (38)
	High speed driving: > 160 (> 100)	260 (38)	260 (38)	280 (41)	280 (41)

Air pressure applies to cold tyres: kPa (psi)					
Tyre size:	Vehicle speed km/h (mph)	1-3 people		Full load	
		Front	Rear	Front	Rear
S60 B5204T5 B5234T3 B5244T3	0-160 (0-100)	200(29)	200(29)	260(38)	260(38)
	High speed driving: > 160 (> 100)	260(36)	260(36)	280(41)	280(41)
"T-spare" T125/80 R 17	0 - 80 (0 - 50)	420 (61)	420 (61)	420 (61)	420 (61)