

Section 7 Springs, shock absorbers, wheels

Group 77 Wheels, tyres, hubs

Wheel

| Dimension | Wheel with aluminium rim | Wheel with steel rim |
|-------------------------------|--------------------------|----------------------|
| | 6.5Jx15x43 | 6.5Jx15x43 |
| | 7Jx16x49 | 7Jx16x49 |
| | 7Jx17x49 | |
| Lateral runout, maximum | 0.4 mm (0.016") | 0.8 mm (0.031") |
| Radial runout, maximum | 0.4 mm (0.016") | 0.7 mm (0.028") |

Tightening torques

| | |
|-------------------|---------------------|
| Wheel studs | 140 Nm (103 ft.lb.) |
|-------------------|---------------------|

Tyre dimensions

| |
|--------------|
| 205/65 R 15 |
| 215/55 R 16 |
| 225/55 R 16 |
| 225/50 R 17 |
| T125/80 R 17 |

Air pressure

| Air pressure, applies to cold tyres: kPa (psi) | | | | | |
|--|---|------------|----------|-----------|----------|
| Tyre size: | Vehicle speed km/h (mph) | 1-3 people | | Full load | |
| | | Front | Rear | Front | Rear |
| All, except 205/65 R 15 | 0 - 160 (0 - 100) | 200 (29) | 200 (29) | 270 (39) | 270 (39) |
| All, except 205/65 R 15 | High speed driving: > 160 (> 100) | 250 (36) | 250 (36) | 270 (39) | 270 (39) |
| 205/65 R 15 | 0 - 160 (0 - 100) | 230 (33) | 230 (33) | 250 (36) | 250 (36) |
| "T-spare" T125/80 R 17 | 0 - 80 (0 - 50) | 420 (61) | 420 (61) | 420 (61) | 420 (61) |